



## Stair Nosing Installation Checklist (UK)

Project Name: \_\_\_\_\_

Installer Name: \_\_\_\_\_

Date: \_\_\_\_\_

### Pre-Installation

- ☐ Check stair surface is clean, dry, and dust-free
- ☐ Confirm stairs are level with no broken edges
- ☐ Measure all tread widths and depths
- ☐ Cut nosing profiles to exact size
- ☐ Dry-fit nosings before fixing
- ☐ Confirm correct profile type (e.g. tile-in, retro-fit)
- ☐ Ensure visual contrast complies with BS 8300

### Installation Process

- ☐ Mark fixing points with pencil or chalk
- ☐ Pre-drill holes if necessary (use correct bit for substrate)
- ☐ Apply PU or MS polymer adhesive evenly
- ☐ Align nosing to stair edge precisely
- ☐ Screw down (if applicable) using appropriate fixings
- ☐ Press in anti-slip insert after fixing
- ☐ Wipe away excess adhesive before curing

### Post-Installation Check

- ☐ Visually inspect all installed nosings
- ☐ Confirm nosings are secure (no lift or flex)
- ☐ Ensure anti-slip inserts are flush and complete
- ☐ Take photographs for record or compliance
- ☐ Clean surface and surrounding area

### Signature

Installer Signature: \_\_\_\_\_

Client/Inspector Signature: \_\_\_\_\_ [www.nationalstairnosings.co.uk](http://www.nationalstairnosings.co.uk)